

DAMT Linear Actuator performances:

Model	Voltage	No Load Speed	No Load Current	Nominal Load	Nominal Current	Maximum Load	Stall Current
	Volt	mm/s	Amp	Kg.	Amp	Kg.	Amp
DAMT 0 A	12.0	10.0	≥0.10	2.50	≥0.50	6.00	≤ 0.65
	24.0	20.0	≥0.20	3.50	≥0.80	12.00	≤ 1.40
DAMT 0 B	12.0	5.0	≥0.10	5.00	≥0.50	13.00	≤ 0.65
	24.0	10.0	≥0.20	8.00	≥0.80	20.00	≤ 1.40
DAMT 0 C	12.0	2.5	≥0.10	10.00	≥0.50	23.00	≤ 0.65
	24.0	5.0	≥0.20	16.00	≥0.80	35.00	≤ 1.40
DAMT 0 E	12.0	2.0	≥0.10	8.00	≥0.50	32.00	≤ 0.65
	24.0	3.5	≥0.20	22.00	≥0.80	60.00	≤ 1.40
DAMT 0 D	12.0	1.2	≥0.10	16.00	≥0.50	52.00	≤ 0.65
	24.0	2.4	≥0.20	40.00	≥0.80	85.00	≤ 1.40
DAMT 1 A	12.0	15.0	≥0.20	5.00	≥0.70	13.00	≤ 1.50
	24.0	30.0	≥0.30	9.00	≥1.20	22.00	≤ 2.80
DAMT 1 B	12.0	6.0	≥0.20	13.00	≥0.70	32.00	≤ 1.50
	24.0	12.5	≥0.30	18.00	≥1.20	50.00	≤ 2.80
DAMT 1 C	12.0	4.0	≥0.20	19.00	≥0.70	45.00	≤ 1.50
	24.0	8.0	≥0.30	40.00	≥1.20	80.00	≤ 2.80
DAMT 1 E	12.0	3.0	≥0.20	26.00	≥0.80	60.00	≤ 1.50
	24.0	5.2	≥0.30	52.00	≥1.20	100.00	≤ 2.80
DAMT 1 D	12.0	1.5	≥0.20	40.00	≥0.80	90.00	≤ 1.50
	24.0	3.0	≥0.30	70.00	≥1.20	150.00	≤ 2.80
DAMT 2 A	12.0	24.0	≥0.25	13.00	≥1.40	33.00	≤ 4.50
	24.0	45.0	≥0.35	27.00	≥2.40	50.00	≤ 8.40
DAMT 2 B	12.0	11.3	≥0.25	22.00	≥1.40	40.00	≤ 4.50
	24.0	20.0	≥0.35	40.00	≥2.40	80.00	≤ 8.40
DAMT 2 C	12.0	6.3	≥0.25	40.00	≥1.40	95.00	≤ 4.50
	24.0	11.8	≥0.35	72.00	≥2.40	140.00	≤ 8.40
DAMT 2 E	12.0	5.0	≥0.25	60.00	≥1.40	140.00	≤ 4.50
	24.0	9.0	≥0.35	100.00	≥2.40	180.00	≤ 8.40
DAMT 2 D	12.0	2.5	≥0.25	85.00	≥1.20	160.00	≤ 4.50
	24.0	4.0	≥0.35	135.00	≥2.40	250.00	≤ 8.40
DAMT 3 A	12.0	32.0	≥0.60	22.00	≥2.20	40.00	≤ 5.00
DAMT 3 B	12.0	13.0	≥0.60	42.00	≥2.20	80.00	≤ 5.00
DAMT 3 C	12.0	7.5	≥0.60	80.00	≥2.20	135.00	≤ 5.00
DAMT 3 E	12.0	5.5	≥0.60	100.00	≥2.20	150.00	≤ 5.00
DAMT 3 D	12.0	3.2	≥0.60	110.00	≥2.20	200.00	≤ 5.00

☀️ Possibility to customized the electric performances as per the customer request. ☀️

**** FOR REFERENCE ONLY ****